

8 7 6 5 4 3 2 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ABBOTT WORKHOLDING PRODUCTS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ABBOTT WORKHOLDING PRODUCTS IS PROHIBITED.

D

C

B

A

3"

1/4"

.250±.010 Slot Depth

2"

.831

.827

Ø 21/32" Thru
Ø 1" C'Bore
2X

A

(3 1/2")

1/8" Gap To \varnothing

R6"

30°

60° x 1.5mm Serrations

7/8" C'Bore Wall

1.181

SECTION A-A

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
± 1/32 .XX ± .015 ± 5°
.XXX ± .005
.XXXX ± .0005

DRAWN
EWP

DATE
11/04/16

MATERIAL
6061

WEIGHT (POUNDS)
10.9

STYLE
Q

DISPOSITION
Released

CUSTOMER:
Stock

SIZE
A

Part Name
KTTB212P3

REV.
B

Abbott Workholding Products
430 McCall Road
Manhattan, KS 66502
785-776-8555
785-587-0004 Fax
800-528-6459
www.abbottworkholding.com
engineering@abbottworkholding.com

DRAWN EWP	DATE 11/04/16
MATERIAL 6061	WEIGHT(POUNDS) 10.9
STYLE Q	DISPOSITION Release

www.abbottworkholding.com
engineering@abbottworkholding.com

REV.
B